



GX630

Honda V-Twin engines offer higher horsepower, improved adaptability, quiet operation, and greater fuel efficiency, not to mention a 3 year warranty.

INTRODUCTION

COMMON APPLICATIONS

Honda's V-Twin range of engines are the cream of the crop, powering Pressure Washers, Water Pumps and Commercial Lawn & Garden Equipment throughout Australia.

The GX630 V-Twin can also be found in Tillers/Cultivators and other Agricultural Equipment, Generators as well as many different applications.

And if it's something more hardcore that you need power for, the GX630 is also used in the Forestry and Construction/Industrial industries.

FUEL EFFICIENT OPERATION

The fuel economy of the GX630 V-Twin is similar to fuel injection, with the simplicity of carburetion ensuring that running this unit is easy on both your pocket and the environment.

It features a digital CDI ignition system with variable timing, as well as a forged steel crankshaft and insert style rod bearings for efficient operation. There's also a rev limiter to protect against damage from over-revving. A hemispherical combustion chamber delivers rapid combustion, and it features Pressure fed crankshaft bearings.

Add a two barrel inner-vent carburetor for more precise fuel metering and a 9.3:1 compression ratio, and you'll be generating high power output without the need for premium fuel.

PROVEN RELIABILITY

The GX630's high capacity pump facilitates consistent oil delivery, and a handy Oil Alert will keep you posted if you look like running dry.

There's a dual cylindrical air filter, and a large diameter air intake on board for superior cooling.

The result is a long-lasting, high-performing and reliable engine.

3 YEAR WARRANTY

Don't forget, all Honda V-Twin Engines are covered by a Honda 3 Year Domestic & Commercial Warranty.

Honda has a network of over 400 authorised dealers around Australia, so should you need parts, accessories, or maintenance done, you're not alone.

All just extra reasons for you to Love Your Honda GX630 V-Twin.

SMOOTH PERFORMANCE

Integrated cylinder and head

Racing inspired forged steel connecting rods

EXCEPTIONALLY QUIET

High capacity 36 blade cooling fan

Aluminium push rods with steel tips - lighter weight, lower vibration, and quieter operation

EASY TO USE AND MAINTAIN

Hour meter standard

Conveniently located controls, with several configurations available based on user preference

Automotive-type spin-on oil filter

EASY STARTING

Automatic mechanical de-compression system

Variable ignition timing

EMISSIONS COMPLIANT

Applicable models meet the strictest world standards, contact Honda for more info

No catalyst necessary

AVAILABLE OPTIONS

High capacity charging systems

A variety muffler options available

Hour meter

SPECS

SPECIFICATIONS

MODEL	GX630
TYPE	Air cooled 4-stroke OHV petrol engine, 90° V-twin design, horizontal shaft
BORE & STROKE	2 / 78 x 72 mm
DISPLACEMENT	688cm ³
COMPRESSION RATIO	9.3:1
NET POWER	15.5 kW (20.8 HP) / 3 600 rpm
CONTINUOUS RATED POWER	10.5 kW (14.1 HP) / 3 000 rpm 12.0 kW (16.1 HP) / 3 600 rpm
MAXIMUM NET TORQUE	48.3 Nm / 4.93 kgfm / 2 500 rpm
IGNITION SYSTEM	Digital CDI with variable ignition timing

STARTING SYSTEM	Electric starter
COOLING SYSTEM	Forced-Air
FUEL CONSUMPTION AT RATED POWER	6.0 L/hr - 3 600 rpm
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Full-pressure
OIL CAPACITY	1.9l
DIMENSIONS	405 x 410 x 438 mm
DRY WEIGHT	44.4kg
RRP	Please contact your local Honda dealer for a great deal. http://dl.hondampe.com.au/

VISIT HONDA POWER EQUIPMENT WEBSITE

For terms and conditions please visit http://about.hondampe.com.au/Terms_and_Conditions

The information in this document is valid as of 31/08/2015. For the most up to date information please visit <http://powerequipment.honda.com.au>