

GENERATORS Powersmart Series

NEW



Model	P2000
Part Number	30653
Number Of Outlets	3
AC Starting (Watts)	2000
Continuous/Rated (Watts)	1600
Engine	OHV
Displacement	111cc
Horsepower**	
Fuel Tank Capacity (L)	3.7
Muffler	Standard
Weight (Kg)	26 kg
Low Oil Protection System	Yes
RCD	
Dimensions L x W x H (cm)	53x36x43
Warranty Domestic	3 Years Limited
Warranty Commercial	

MANOEUVRABILITY

- Twin grip, 2 person handle for easier lifting

EASE OF USE

- Twin grip, 2 person handles for easier lifting
- Pull Start
- Easy Starting, long life overhead valve engine
- Overload alarm, circuit breaker and low oil protection

* Terms and conditions apply see owners manual for details.



GENERATORS Powersmart Series

NEW



StatStation™

Everything you need to know
at the touch of a button.



Model	P3000
Part Number	30654
Number Of Outlets	3
AC Starting (Watts)	3000
Continuous/Rated (Watts)	2600
Engine	OHV
Displacement	171cc
Horsepower**	
Fuel Tank Capacity (L)	5.7
Muffler	Standard
Weight (Kg)	44 kg
Low Oil Protection System	Yes
RCD	
Dimensions L x W x H (cm)	66x36x53
Warranty Domestic	3 Years Limited
Warranty Commercial	

MANOEUVRABILITY

- Twin grip, 2 person handle for easier lifting
- Retractable handles and wheels making it easy to move

EASE OF USE

- Statstation™ Digital Display - Displays power usage, total unit lifetime hours, and maintenance reminders.
- Pull Start
- USB Charging Port
- Parallel connector port - double your power output (Optional kit to join two sets together)

* Terms and conditions apply see owners manual for details.





Model	Elite 3500/3000
Part Number	30617
Number Of Outlets	3
AC Starting (Watts)	3500
Continuous/Rated (Watts)	3000
Engine	Briggs & Stratton 1150 Series™
Displacement	250cc
Horsepower**	8.5
Fuel Tank Capacity (L)	15
Muffler	Yes - Spark Arrestor Type
Weight (Kg)	63 kg
Low Oil Protection System	No
RCD	Yes
Dimensions L x W x H (cm)	66x45x59
Warranty Domestic	2 Years Limited
Warranty Commercial	1 Year Limited

MANOEUVRABILITY

- T-Style collapsible padded handle
- Never-Flat wheels
- Heavy duty roll-frame suits any worksite

STRENGTH & RIGIDITY

- 32mm thick, weld free tube frame for a stronger build
- Engine mounted to frame through high tension rubber engine mounts for reduced vibration
- Durable steel fuel tank with fuel gauge

EASE OF USE

- Pull Start
- 2 x IP44 Water resistant sockets with 12 Volt/5A Auxiliary power outlet
- Automatic Voltage regulator and 16A Circuit Breaker

† Equivalent Max kVA: some manufacturers give ratings in kVA by adding 25% to the power rating. This figure is for comparison with these values.

* Terms and conditions apply see owners manual for details.

GENERATORS Elite



StatStation™

Everything you need to know
at the touch of a button.



Model	Elite 6250/5300
Part Number	30619
Number Of Outlets	3
AC Starting (Watts)	6300
Continuous/Rated (Watts)	5300
Engine	Briggs & Stratton 2100 Series™
Displacement	420cc
Horsepower**	12
Fuel Tank Capacity (L)	28
Muffler	Yes - Spark Arrestor Type
Weight (Kg)	91 kg
Low Oil Protection System	Yes
RCD	Yes
Dimensions L x W x H (cm)	72x54x63
Warranty Domestic	2 Years Limited
Warranty Commercial	1 Year Limited

MANOEUVRABILITY

- T-Style collapsible padded handle
- Never-Flat wheels
- Heavy duty roll-frame suits any worksite

STRENGTH & RIGIDITY

- 38mm thick, weld free tube frame for a stronger build
- Engine mounted to frame through high tension rubber engine mounts for reduced vibration
- Durable steel fuel tank with fuel gauge

EASE OF USE

- Statstation™ Digital Display - Displays power usage, total unit lifetime hours, and maintenance reminders.
- Pull Start
- 2 x IP44 Water resistant sockets with 12 Volt/5A Auxiliary power outlet
- Automatic Voltage regulator and 25A Circuit Breaker

† Equivalent Max kVA: some manufacturers give ratings in kVA by adding 25% to the power rating. This figure is for comparison with these values.

* Terms and conditions apply see owners manual for details.





StatStation™

Everything you need to know
at the touch of a button.



Model	Elite 9500/7000
Part Number	30620
Number Of Outlets	3
AC Starting (Watts)	9500
Continuous/Rated (Watts)	7000
Engine	Briggs & Stratton 2100 Series™
Displacement	420cc
Horsepower**	13.5
Fuel Tank Capacity (L)	28
Muffler	Yes - Spark Arrestor Type
Weight (Kg)	104 kg
Low Oil Protection System	Yes
RCD	Yes
Dimensions L x W x H (cm)	72x54x63
Warranty Domestic	2 Years Limited
Warranty Commercial	1 Year Limited

MANOEUVRABILITY

- T-Style collapsible padded handle
- Never-Flat wheels
- Heavy duty roll-frame suits any worksite

STRENGTH & RIGIDITY

- 38mm thick, weld free tube frame for a stronger build
- Engine mounted to frame through high tension rubber engine mounts for reduced vibration
- Durable steel fuel tank with fuel gauge

EASE OF USE

- Statstation™ Digital Display - Displays power usage, total unit lifetime hours, and maintenance reminders.
- Electric Start for easy ignition
- 2 x IP66 Water resistant sockets with 12 Volt/5A Auxiliary power outlet
- Automatic Voltage regulator and 32A Circuit Breaker

† Equivalent Max kVA: some manufacturers give ratings in kVA by adding 25% to the power rating. This figure is for comparison with these values.

* Terms and conditions apply see owners manual for details.